

Homespring™ Central Water Purifier



homespring™

Technical Specifications

Maximum Peak Flow Rate (LPM/USgal)	Up to 42/11
Maximum Continuous Flow Rate (LPM/USgal)	17/4.5
Minimum Temperature (°C/°F)	> 0/32
Maximum Temperature	> 38/100
Approximate Flush Volume (litres/USgal)*	45/12
Typical System Efficiency*	95%
Controller Voltage (VAC)	120/230
Bacteria Removal**	> 99.99999%
Virus Removal**	> 99.999%
Cyst Removal**	> 99.99%

* Depends upon model, water quality and flowrate

**Please see certification and testing data for more information

Applicable to model #UF 207, UFC 207, UF 209, UFC 209, UF 211, UFC 211



Homespring™ model number

UFC 211

UF 211

Maximum rated peak flow in gallons (litres) per minute

11 GPM
(42 LPM)

Maximum rated continuous flow in gallons (litres) per minute

4.5 GPM
(17 LPM)

Approximate water volume treated annually in gallons (litres)

130,000 gallons
(0.49 millions litres)

Estimated carbon filter capacity in gallons (litres)

130,000 gallons
(0.49 millions litres)

Number of people in home

5 or more

Number of bathrooms

2.5 – 3.5

Maximum ambient temperature

60° (140°F)

Homespring™ controllers

All systems have the capacity to effectively filter water from either surface/lake, well, or municipal water supplies.

Additional pre-filtration may be required depending on water source.



Advanced plus